## pegasus industries inc



## **CATALOG TABLE OF CONTENTS**

<u>Item</u>	Page number
Fertilizer spreaders	1
Landscape rakes	2
Scrape blades	2
Hay bale fork	2
Box blades	3
One bottom plows	3
Rotary mowers	4
Log splitters	5
Disc harrows	6-8
Finishing mowers	9
Post hole diggers	10
Rotary tillers	10
Cement mixers	11
Boom poles	11
Canopies	11
Bale spears	12
Quick hitches	12
Scoops	13
Carry alls	13
One row cultivators	13
Front end loaders	14



- \*Pegasus fertilizer spreaders offer top quality and low price - a great value!
- \*The poly hopper won't rust like metal hoppers so the machine lasts much longer.
- \*Available in 250 liter and 500 liter sizes.
- \*Category I 3 point hitch hook up.
- \*Includes PTO shaft.

# **Fertilizer Spreaders**

# **Pegasus**Premier

Pegasus Premier products are the top quality available. You can still expect to pay less for Premier than other brands of the same quality.



The Pegasus Premier fertilizer spreader offers a heavy duty frame supporting a thick poly no-rust hopper. Bracing on the top of the hopper provides support for your seed or fertilizer bag while filling the spreader. Landscape professionals or farmers will appreciate the construction and features of this Premier product.



Model#	Width	Approx. Wt.
LR-60	5 Foot	200 lbs
LR-72	6 Foot	220 lbs
LR-84	7 Foot	255 lbs

## Landscape Rakes

The rake tines are manufactured from high carbon steel, heat treated and tempered to give a strong positive rake action and long life. Multi tine locks hold rake tines solidly in place. Rotates 360 degrees for different angle positions.

## Tilt and Angle Blade

The SB-6 and SB-7 blades are excellent all around landscaping blades. They come standard with reversible bolt-on cutting edges. The 6 tilt positions makes them perfect for ditching and trenching. The 6 forward and 6 reverse angle positions can be used for forward scraping or backfilling.



- ⇒ Angles, Reverses, and Tilts
- $\Rightarrow$  <u>6</u> tilt positions
- $\Rightarrow$  <u>6</u> forward and reverse angle positions

OF MANY STATES	

<u>Model#</u>	Width	Approx. Wt.
SB6	6 Foot	290 lbs
SB7	7 Foot	355 lbs

## BF1 Hay Bale Fork



Our hay bale forks are made to move round hay bales with ease. The forks can be used for a variety of farming needs and have the standard category 1 hook up for 3 point hitch tractors. The forks are  $54^{\prime\prime}$  in length.

Approximate weight 120 lbs.



Model#	Width	Approx. Wt.
CBB400	4 Foot	170 lbs
CBB500	5 Foot	255 lbs

## **Compact Box Blade**

The compact line is a new concept designed with the price conscious consumer in mind. The same features you need in a box scrape are available at a lower price. You can choose between 3 different ripper heights with the pull of a pin. Comes with standard replaceable weld-on blade.

- ⇒ Easy pin adjustment
- ⇒ Weld on blade



Width	Approx. Wt.
4 Foot* *	290 lbs
5 Foot	405 lbs
6 Foot	445 lbs
7 Foot	530 lbs
	4 Foot** 5 Foot 6 Foot

#### **Box Blade**

The Pegasus box blade stands out above its competition. Built with quality materials and expert workmanship, the box blade is engineered to give maximum scraping action with minimum side leakage. The rippers have three position holes at the top away from the points of stress. This makes them easier to change, less susceptible to jamming and much stronger than rippers with notches. Both the front and rear blades are  $1/2" \times 6"$  forged steel, reversible for double wear time.

- ⇒ Easy pin adjustment
- ⇒ Bolt on blade
- \* \* 4' has front bolt on blade only

### One Bottom Plows

Quality workmanship and unique design separate the Pegasus one bottom plows from the rest of the field. Ideal for the small farm, these plows are available in three sizes.



<u>Model#</u>	Description	<u>Approximate Wt.</u>
1BP-12	12" One Bottom Plow	150 lbs
1BP-14	14" One Bottom Plow	152 lbs
1BP-16	16" One Bottom Plow	154 lbs



# **Rotary Mowers**



Our Premium **blade carriers** have never dented or bent as with the thinner dished type blade carriers. It is the best design in the industry when it comes to reliable operation in the field. Should you accidentally hit something in the field you will have the 1/2" thick plate steel blade carrier to get you through with no damage to the cutter or it's components.

Constructed of 1/2" plate steel with a splined hub. Hub is welded to top and bottom of carrier for strength and to protect your drive train from damage during field operation.

Why settle for what others call the "stump jumper". Get the one that really takes the toughest of your cutting needs without damage to the blade carrier or drive train.

			Blade		
Model#	Size	Wheel	Carrier	Deck	Approximate Wt.
RM4	4′	Solid rubber	Oval	14 Gauge	305 lbs
RM4L	4′	Laminated	Oval	14 Gauge	310 lbs
RM5	5′	Solid rubber	Oval	12 Gauge	400 lbs
HRM5	5′	Laminated	Round	8 Gauge	470 lbs
HRM6	6′	Laminated	Round	8 Gauge	560 lbs

- $\Rightarrow$  All cutters come with 2 heat-treated, free swinging blades.
- ⇒ Blade carriers are made of 1/2" thick solid plate steel.
- ⇒ Round blade carrier has placing for up to 4 blades.
- $\Rightarrow$  Oval blade carrier has placing for up to 2 blades.
- ⇒ All cutters come with 40 horsepower gearbox.



## LSE22

- \* 6.5 HP Engine
- \* 22 Ton Capacity
- \*26" log capacity
- \*Splits horizontally or vertically
  - \* Trailer ball hitch

# **LOG SPLITTERS**



## **LS322**

- \* 3 Point hitch hook-up
  - \*22 ton capacity
  - \*26" log capacity
- \*4" diameter cylinder





## Single Section Harrow

These disc harrows are single section harrows designed for small farm tractors. They are made to ensure dependable service and long life. The steel frame has three adjustment positions for varying the cutting angle. Greasable iron bearings are standard.

 Model#
 Discs
 Size
 Length
 Approx. Wt.

 DH816
 8
 16"
 52"
 250 lbs

 DH1016
 10
 16"
 62"
 295 lbs

Iron Bearing







## Disc Harrow

These disc harrows are adjustable double section disc harrows designed for 20 to 50 horse power tractors. They are made on a steel frame and can be ordered with either greaseable iron bearings or sealed anti-friction bearings.

Sealed Bearing



	#	Disc		Cutting	
Model#	Disc	Size	Bearing	Width	Approx. Wt.
DH1216	12	16"	Iron	4 Foot	345 lbs
DH1218	12	18"	Iron	4 Foot	351 lbs
DH1616	16	16"	Iron	5 ½ Foot	437 lbs
DH1618	16	18"	Iron	5 ½ Foot	445 lbs
DH2018	20	18"	Iron	6 ½ Foot	560 lbs
DH2020	20	20"	Iron	6 ½ Foot	570 lbs
DH1216B	12	16"	Sealed	4 Foot	285 lbs
DH1218B	12	18"	Sealed	4 Foot	291 lbs
DH1616B	16	16"	Sealed	5 ½ Foot	377 lbs
DH1618B	16	18"	Sealed	5 ½ Foot	385 lbs
DH2018B	20	18"	Sealed	6 ½ Foot	565 lbs
D2020B	20	20"	Sealed	6 ½ Foot	575 lbs





## Heavy Disc Harrow

Heavy Frame Sealed Bearings 3" x 3" Harrow Arms 7 ½" or 9" Spacing Pin Adjustment 1" Square Axle 6 to 8 Foot Widths Category 1, 3Pt. Hitch

## Sealed Bearing



	#	Disc		Cutting	
Model#	Disc	Size	Spacing	Width	Approx. Wt.
HH1620B-9	16	20"	9"	6 Foot	850 lbs
HH2020B	20	20"	7 ½ "	6 ½ Foot	850 lbs
HH2020B-9	20	20"	9"	7 Foot	870 lbs
HH2420B	24	20"	7 1/2 "	8 Foot	885 lbs





## **Finishing Mowers**

- \* Rear discharge
- \* 2 belt design for less slippage and easy service
- \* 4 adjustable wheels
- \* Floating hitch to minimize scalping
- \* 3 cutting blades

FM600: 5 foot cutting width

FM720: 6 foot cutting width





## Post Hole Diggers

Model#	Description
DIG1	Post hole digger unit
A6	6" Standard Auger
Α9	9" Standard Auger
A12	12" Standard Auger



## Nardi Tillers

- ⇒ Category 1 hitch
- ⇒ Depth control by skids

## \*Shear pin PTO and Chain driven:



<u>Model#</u>	Size	HP min/max	# of Tines
ZAL-105	42"	15 to 20	20
ZAL-125	50"	20 to 25	24
ZAL-145	58"	25 to 30	28
ZAD-125	50"	20 to 25	24
ZAD-165	65"	45 to 55	32
ZAD-185	74"	50 to 55	36

## \*Slip Clutch and Gear driven:

Model#	Size	HP min/max	# of Tines
ZE/A-165	65"	40 to 65	32
ZE/A-185	74"	50 to 65	36
ZE/A-205	81"	60 to 65	40
Z6/D-210	83"	60 to 80	48
Z6/D-235	93"	65 to 80	54
ZRS-285	113″	130 to 180	66





## Agric Tillers

- ⇒ Category 1 hitch
- ⇒ Depth control by skids
- \*Shear pin PTO and Chain driven:

Model#	Size	HP min/max	# of Tines
ALJ - 40	41"	17 to 20	20
ALJ - 45	47"	20 to 22	24



#### **Cement Mixer**

Internal paddles for uniform mixing and clean dumping.

Hydraulic top link cylinder provides positive dump control. Roller chain drives mixing drum. Adjustable hitch for easy hook-up to most tractors. 17.5" drum opening, 11 gauge steel drum and 5 cu. Ft. capacity.

\*PTO included



## **Boom Pole**

Turn your tractor into a small crane. A boom helps load and unload heavy objects from trucks or trailers and pull posts. Lift capacity 800 lbs.



Pegasus
Industries inc.



## Canopies

Made of polyethylene impregnated with UV protection to prevent fading. Mounts on all square and rectangular ROPS. 44" wide and 61" long. Mounted on 3" x 4" tubing for



## Bale Spear

Features tapered forged spring steel spears designed for hard center bales allowing easy penetration and withdrawal. A special tapered socket provides support for spear.

Load capacity 1000 lbs.



### Quick Hitch

Maximum 45 HP recommended. Heavy duty steel construction. 26 inch width, adjustable top link ball bracket. Includes 7/8" mounting pins and adaptor bushings, and 27 1/4" at lift arm spacing.



## **Pegasus** Premier

### Quick Hitch

Pegasus Premier products are the top quality available. You can still expect to pay less for Premier than other brands of the same quality.

This quick hitch allows you to attach and release implements from the comfort of the tractor seat. Features spring loaded ergonomic handle with auto release system.





## Scoop

Width 24", reinforced tubular steel frame, carbon steel bucket has 9/32' cutting edge. Bucket balances on center-mount frame busing for easy dumping. Spring loaded latch locks, tips and resets from the tractor seat. Constructed of 2 3/8" tube and 2 ¼" angle iron frame.



## Pegasus Industries inc.



## Carryall

An all-purpose tool, can be floored. A great help in moving heavy, bulky items with ease. 27" wide and 32" in length.

Load Capacity 500 lbs.



#### Cultivator

A heavy-duty, one-row cultivator for any size job. Close-up mounted for better control. Heavily welded construction features reversible shovels and adjustable spacing from end to end.



Complete loaders include: 2 bucket cylinders and 2 lift cylinders, hoses, parking stand, grill guard, bucket, mounting kit and joystick control valve. Loaders are packaged individually on wooden pallets. Quick attach buckets are Bobcat skid steer compatible.

## Front end loaders

Model # <u>Fits</u> <u>Bucket</u>

<u>Loaders for Branson Tractors</u> (available May 2007)

LB10 10 series 62" quick attach LB20 20 series 62" quick attach LB30 30 series 72' quick attach

**Options** 

Self leveling loader

Fender mount joystick w/cable

**Loaders for Montana Tractors** 

LM19 5720C & 5740C 72" quick attach

LM18 4920 & 4940 72" quick attach

**Loaders for FarmTrac Tractor** 

LF19 550DTC 72" quick attach

**Loaders for Farm Pro & Jinma Tractors** 

LJ17 Farm Pro 2010/2510/3010 60" quick attach

Jinma 254/354

Bobcat Style Quick Attach Buckets are STANDARD

